

L Number	Hits	Search Text	DB	Time stamp
1	2	(back adj oxidation) same (oxygen with chlorine)	USPAT; US-PGPUB	2004/06/21 13:13
2	144	(oxidation with oxide) same (oxygen with chlorine)	USPAT; US-PGPUB	2004/06/21 13:14
3	48	((oxidation with oxide) same (oxygen with chlorine)) and gate	USPAT; US-PGPUB	2004/06/21 13:14
4	10	((((oxidation with oxide) same (oxygen with chlorine)) and gate) and silicide and polysilicon	USPAT; US-PGPUB	2004/06/21 13:14
5	9	(((((oxidation with oxide) same (oxygen with chlorine)) and gate) and silicide and polysilicon) and @ad<20021031	USPAT; US-PGPUB	2004/06/21 13:14

US-PAT-NO: 6660587

DOCUMENT-IDENTIFIER: US 6660587 B2

TITLE: Method for forming a gate electrode
in a semiconductor device

----- KWIC -----

Abstract Text - ABTX (1):

A semiconductor device and method of production are disclosed, the method including forming a preliminary gate electrode on a semiconductor substrate, the preliminary gate electrode including a gate oxide layer pattern and a conductive layer pattern stacked on the gate oxide layer pattern, and performing a re-oxidation process for curing damage of the semiconductor substrate and/or a sidewall of the conductive layer pattern, when the preliminary gate electrode is formed by forming an oxide layer on an outer surface of the preliminary gate electrode and on the semiconductor substrate, by supplying an oxygen gas and a chlorine-including gas while restraining a thickness of the gate oxide layer pattern from being increased; and the semiconductor device comprising a preliminary gate electrode formed on a semiconductor substrate, the preliminary gate electrode including a gate oxide layer pattern and a conductive layer pattern stacked on the gate oxide layer pattern, and a re-oxidized semiconductor substrate and/or a sidewall of the conductive layer pattern, with damage cured therein by supplying an oxygen gas and a chlorine-including gas while restraining a thickness of the gate oxide layer pattern from being increased.

Brief Summary Text - BSTX (9):

To achieve the first preferred embodiments of present invention, a preliminary gate electrode including a gate oxide layer pattern and a conductive layer pattern stacked on the gate oxide layer pattern is formed on a semiconductor substrate. A re-oxidation process is performed for forming the gate electrode by forming an oxide layer on an outer surface of the preliminary gate electrode and the semiconductor substrate, and supplying an oxygen gas and a chlorine-including gas into a reactor while restraining a thickness of the gate oxide layer pattern from being increased.

Brief Summary Text - BSTX (10):

To achieve the second preferred embodiments of the present invention, a preliminary cell gate electrode is formed on a semiconductor substrate. The preliminary cell gate electrode includes a tunnel oxide layer pattern, a first conductive layer pattern stacked on the tunnel oxide layer pattern, a dielectric interlayer pattern stacked on the first conductive layer pattern, and a second conductive layer pattern stacked on the dielectric interlayer. A re-oxidation process is performed for forming an oxide layer on an outer surface of the preliminary cell gate electrode and on the semiconductor substrate by supplying an oxygen gas and a chlorine-including gas while restraining a thickness of the tunnel oxide layer pattern and the dielectric interlayer pattern from being increased.

Brief Summary Text - BSTX (11):

According to another preferred embodiment of the present invention, a stacked structure of a tunnel oxide layer pattern, a first

silicon layer
pattern for a floating gate, and a nitride layer pattern
are formed on a
semiconductor substrate. A trench is formed by etching the
semiconductor
substrate using the stacked structure as an etching mask.
A field oxide layer
is formed for burying the trench. A dielectric interlayer
and a second silicon
layer for a control gate are sequentially formed on the
first silicon layer
pattern. A preliminary cell gate electrode having a
stacked structure of the
tunnel oxide layer pattern, the first silicon layer
pattern, a floating gate
pattern, an dielectric interlayer pattern, and the second
silicon layer
pattern, is formed by etching predetermined portions of the
control gate and
the dielectric interlayer. A re-oxidation process is
performed for forming an
oxide layer on an outer surface of the preliminary cell
gate electrode and on
the semiconductor substrate by supplying an oxygen gas and
a chlorine-including
gas onto the semiconductor substrate, including the cell
gate electrode, while
restraining a thickness of the tunnel oxide layer pattern
and the dielectric
interlayer pattern from being increased.

Brief Summary Text - BSTX (12):

Since the oxygen gas and the chlorine-including gas are
used for the
re-oxidation process, the thickness of the gate oxide layer
pattern can be
restrained from being increased so that the thickness
difference of the gate
oxide layer pattern in each gate electrode can be reduced.

Detailed Description Text - DETX (2):

Disclosed is a method for forming a gate electrode,
capable of restraining a
thickness of a gate oxide layer pattern from being
increased when a
re-oxidation process is carried out for forming the gate